

# DIESEL TREATMENT

11/08/2023  
70311

*Cleans the complete fuel system, increases cetane number and restores power and performance. Improves combustion and reduces fuel consumption. Lubricates the diesel pump in case of low sulphur fuel.*

## APPLICATIONS

For all diesel engines, including common rail, with or without turbochargers. Add the content of one bottle to the fuel tank, prior to filling. The contents of one bottle is sufficient for 50 to 60 litres of diesel fuel.

## FEATURES

Cleaning action: superior cleaning of the fuel system

## PERFORMANCE

/ /

## TYPICAL CHARACTERISTICS

| Test                            | Method     | Unit               | Average results |
|---------------------------------|------------|--------------------|-----------------|
| Density at 15°C                 | ASTM D4052 | g/ml               | 0.860           |
| Kinematic viscosity at 40°C     | ASTM D445  | mm <sup>2</sup> /s | 13.4            |
| B.N. (HClO <sub>4</sub> method) | ASTM D2896 | mg KOH/g           | 1.2             |
| Flashpoint PMCC                 | ASTM D93   | °C                 | 130             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION