PNEUMA ISO 32

This oil is destined for the lubrication of pneumatic tools. It contains additives to enhance adhesion, anti-rust activity and an emulsifier to absorb moisture that can be present in the oil. Furthermore, it contains anti-wear and extreme-pressure additives.

ZASTOSOWANIA

This lubricant can be used in tools driven by compressed air, like for instance drilling equipment. This ISO 32 grade can be used in high-speed tools.

CECHY

Extreme pressure properties : good EP properties.
Anti-foam properties : adequate anti-foam performance.

SPECYFIKACJA

DIN 51502 D

ISO 6743-11 CLASS LP

TYPOWE CECHY

Test	Metoda	Jednostka	Średni wynik
Gęstość w temp. 15°C	ASTM D4052	g/ml	0.876
Lepkość kinematyczna przy temp. 40°C	ASTM D445	mm²/s	33.1
Lepkość kinematyczna w temp. 100°C	ASTM D445	mm²/s	5.82
Indeks lepkości	ASTM D2270		119
Temperatura krzepnięcia	ASTM D6892	°C	-30
Tempera zapłonu metodą Clevelanda	ASTM D92	°C	208

Zastrzegamy sobie prawo do modyfikowania ogólnych charakterystyk naszych produktów, aby umożliwić naszym klientom czerpanie maksymalnych korzyści z najnowszych odkryć techniki.

CHAMPION CHEMICALS NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

The CHAMPION brand and design are registered trademarks of Champion Chemicals NV – Made in Belgium