

# CHAMPION COMPRESSOR OIL

## ISO 32

*This is a compressor oil made of highly refined base oils and additives to prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.*

### APPLICATIONS

*This oil is particularly recommended for the lubrication of air compressors with high temperatures or when an oil according to the DIN classification VDL is required.*

### FEATURES

*Anti-wear and oxidation stability: superior protection*

*Anti-foam properties: adequate anti-foam performance*

### PERFORMANCE

**DIN** 51506 VDL **PNEUROP** DIN 51.352

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.873
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.5
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.4
Viscosity index	ASTM D2270		99
A.N. [Colorimetric]	ASTM D974	mg KOH/g	0.08
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

