

WOLF OFFICIALTECH OW-20 UHPD D-FE

14/04/2025
65656

This full synthetic engine oil has been developed to offer high performance and ultimate protection of the latest Daimler Truck engines with a DTFR 15C140 engine oil specification. Its particular formulation gives this low SAPS engine oil extraordinary features.

APPLICATIONS

This low SAPS engine oil meets and exceeds the newest DTFR 15C140 (former MB 228.71) engine oil specification in OW-20 viscosity grade.

FEATURES

Aftertreatment protection: full aftertreatment system protection
Fuel economy: superior fuel economy and CO2 reduction
Total engine protection: outstanding engine cleanliness and durability

SPECIFICATIONS

DTFR 15C140

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.847 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 39 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 8.5 |
| Viscosity index | ASTM D2270 | | 167 |
| B.N. (HClO4 method) | ASTM D2896 | mg KOH/g | 9.4 |
| Pour point | ASTM D6892 | °C | -45 |
| Sulfated Ash | ASTM D874 | Mass % | 0.86 |
| Flash Point COC | ASTM D92 | °C | 218 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

