

CHAMPION ACTIVE DEFENCE

SAE 40 SF/CD

Monograde engine oil for the lubrication of gasoline and diesel engines of passenger cars, with or without turbo. This oil is characterized by a combination of good detergent and dispersant properties, together with a low ash content.

APPLICATIONS

This oil is suitable for the lubrication of gasoline and diesel engines from 1980 to 1989.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

| | | | |
|-----|-----------|----|-------|
| API | SF/CD | MB | 226.0 |
| MIL | L-46152 B | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|--------------------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.895 |
| Kinematic viscosity at 40°C | ASTM D445 | mm ² /s | 145 |
| Kinematic viscosity at 100°C | ASTM D445 | mm ² /s | 14.1 |
| Viscosity index | ASTM D2270 | | 94 |
| B.N. [HClO4 method] | ASTM D2896 | mg KOH/g | 5.6 |
| Pour point | ASTM D6892 | °C | -33 |
| Flash Point COC | ASTM D92 | °C | 250 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

