

CHAMPION COLDCLEANER

This is a solvent and cleaning product, based on an aliphatic solvent, emulsifiers and tensio-actives. The product is emulsifiable with water and specifically used for the removal of oily, greasy and asphalt pollutions.

APPLICATIONS

This product is used to clean engines, machines and workshops. Suitable for high pressure steam cleaner. Eliminates the paraffinic protection coating of the bodywork. It is necessary to apply the product in "pure state" on the part to clean with a brush. To clean an engine or the floor of a garage, one should apply the product with a brush and then rinse with a high pressure cleaner.

FEATURES

Cleaning properties: Efficient removal of oily contaminants

PERFORMANCE

ISO 6743/10

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.824
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	1.53
Flashpoint PMCC	ASTM D93	°C	63

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

