

CHAMPION MOTO HP 2T

Thanks to its stable mineral base oils and advanced additive package, this two-stroke motorcycle engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of motorcycle enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for the engines of 2-stroke motorcycles. Please follow the dosage recommendations of the equipment manufacturer.

FEATURES

Engine protection: Extended motorcycle lifespan thanks to the oil's protective properties.

: Protects the original riding comfort.

Simpler fluid management thanks to the oil's broad applicability.: simpler fluid management thanks to the oil's broad applicability

PERFORMANCE

API

TC

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	56.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.2
Viscosity index	ASTM D2270		115
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	1.7
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

