

# LIFE EXTENSION

## 75W80 GL 5

*This is an extreme-pressure lubricant for gear boxes, specially formulated to satisfy the highest service conditions: high speed, shockloads and high torque at low speeds.*

### APPLICATIONS

*It is recommended for all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles.*

### FEATURES

*Frictional properties : smooth shift performance.*

*Anti-wear protection : long transmission life.*

*Extended oil life : proven resistance to oil degradation.*

### SPECIFICATION LEVEL

<b>API</b>	GL-5	<b>MIL</b>	MIL-L-2105 D
<b>MIL</b>	MIL-L-2105 C		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.869
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	49.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.23
Viscosity index	ASTM D2270		171
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	65000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

**CHAMPION®**