

# CHAMPION COMPRESSOR OIL

## ISO 68

*This is a compressor oil made of highly refined base oils and additives to prevent oxidation, corrosion and foaming. It meets the strict requirements of the PNEUROP-oxidation test.*

### APPLICATIONS

*This oil is particularly recommended for the lubrication of air compressors with high temperatures or when an oil according to the DIN classification VDL is required. It may also be used in vacuum pumps. This lubricant is capable of providing oil maintenance of up to 2000 hours (where allowed by the manufacturer).*

### FEATURES

*Anti-wear and oxidation stability: superior protection*

*Anti-foam properties: adequate anti-foam performance*

### PERFORMANCE

<b>DIN</b>	51506 VDL	<b>PNEUROP</b>	DIN 51.352
------------	-----------	----------------	------------

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	66.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	8.7
Viscosity index	ASTM D2270		101
A.N. [Colorimetric]	ASTM D974	mg KOH/g	0.08
Pour point	ASTM D6892	°C	-21
Flash Point COC	ASTM D92	°C	253

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

