

CHAMPION MOTO HP 2T SNOWSCOOTER

Thanks to its stable synthetic blend of base oils and advanced additive package, this two-stroke snowscooter engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of snowscooter enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for the engines of 2-stroke snowscooters. Please follow the dosage recommendations of the equipment manufacturer.

FEATURES

: Extended snowscooter lifespan thanks to the oil's protective properties.

: Protects the original riding comfort.

Simpler fluid management thanks to the oil's broad applicability.: simpler fluid management thanks to the oil's broad applicability

PERFORMANCE

API	TC	NMMA	TC-W3
JASO	FC		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	42.7
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.9
Viscosity index	ASTM D2270		158
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	5.1
Pour point	ASTM D6892	°C	-42
Flash Point COC	ASTM D92	°C	104
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

