

WOLF TRACTOFLUID 50

14/04/2025
3119

Full synthetic oil designed to deliver exceptional performance for wet brakes across a wide temperature range and under all operating conditions. It provides superior wear protection, reduces friction (hence lower fuel consumption), and minimizes brake noise.

APPLICATIONS

This oil is primarily intended for the Volvo "standard 97304 (WB 102)" applications. But can also be used for automatic transmissions, hydraulic systems, wet brakes, convertors for tractors, forklifts and different off-highway equipment providing the viscosity grade 75W80 is recommended.

FEATURES

Anti-wear and oxidation stability: reliable protection of all parts

SPECIFICATIONS

API	GL-4
DIN	51524 T3 HVLPD
AGCO/ALLIS	821 XL
CASE	MAT 3505/3525/3526
CASE	MAT 3540
CASE	MS 1206/1207/1209
CLAAS	RENAULT AGRICULTURE
FORD	ESN-M2C134 D
FORD	FNHA-2-C-201.00
JD	J20 D
KUBOTA	SUPER UDT ²
KUBOTA	UDT
MC CORMICK	HTX
MF	M 1143
MF	M 1145
NH	NH 410B/C
VALTRA	G2-08
VALTRA	G2-B10
VOLVO	97303/WB101
VOLVO	97304/WB102
ZF	TE-ML 03E
ZF	TE-ML 05F
ZF	TE-ML 06D
ZF	TE-ML 06K
ZF	TE-ML 06N
ZF	TE-ML 06R
ZF	TE-ML 17E
ZF	TE-ML 21F

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.857
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	40.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.7
Viscosity index	ASTM D2270		161
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-48
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	23700

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

