

MOTO PERFORMANCE 4T 15W50

09/10/2023
29136

Thanks to its advanced additive package, this four-stroke motorcycle engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of motorcycle enthusiasts looking for optimal riding comfort. Its high viscosity at high temperatures will ensure complete engine protection in hot riding conditions.

APPLICATIONS

This lubricant is developed for the engines, transmissions and wet clutches of four-stroke motorcycles. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Engine protection: outstanding engine cleanliness and durability.

Anti-wear and oxidation stability: superior protection.

Temperature stability: superior viscosity stability.

PERFORMANCE

API

SL

JASO

MA2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.852
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	116.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	17.8
Viscosity index	ASTM D2270		170
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	6.1
Pour point	ASTM D6892	°C	-36
Colour	VISUAL		BROWN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION