

# WOLF IN-OUTBOARD 4T 25W40

11/08/2023  
1956

This is a semi-synthetic 4-stroke motor oil, specifically designed to meet the requirements of the NMMA FC-W specification. This oil procures an increased protection against corrosion, even in a salt water environment. It also contains a unique anti-wear package based on molybdenum/zinc technology.

## APPLICATIONS

This oil is specifically destined for the lubrication of modern 4-stroke outboard and inboard engines (e.g. Mercury Marine, Yamaha). These applications are usually described as "sterndrive & inboard". It can also be used in older 4-stroke outboard engines.

## FEATURES

Total engine protection: Outstanding engine cleanliness and durability

## PERFORMANCE

API	SJ	NMMA	FC-W
API	SL		

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	91.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	13.8
Viscosity index	ASTM D2270		155
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -10°C	ASTM D5293	mPa.s	6100
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

