

# CHAMPION COMPETE ATF DEXRON III

This ATF fluid has a high viscosity index to ensure great fluidity on engine start and guaranteed component protection at high temperatures.

## APPLICATIONS

Can be used to service a range of different automatic transmission systems, torque convertors, power steering systems and hydraulic circuits.

## FEATURES

Frictional properties: smooth shift performance  
Anti-wear protection: extended transmission life

## SPECIFICATIONS

<b>ALLISON</b>	C4	<b>FORD</b>	ESP-M2C166-H
<b>CATERPILLAR</b>	TO-2	<b>FORD</b>	MERCON
<b>DTFR</b>	13C120	<b>GM</b>	DEXRON III-H
<b>FORD</b>	ESP-M2C138-CJ	<b>MB</b>	236.2

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.849
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	32.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.82
Viscosity index	ASTM D2270		181
Pour point	ASTM D6892	°C	-51
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	14140
Flash Point COC	ASTM D92	°C	198
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

