

CHAMPION COMPETE ATF DEXRON III

This ATF fluid has a high viscosity index to ensure great fluidity on engine start and guaranteed component protection at high temperatures.

APPLICATIONS

Can be used to service a range of different automatic transmission systems, torque convertors, power steering systems and hydraulic circuits.

FEATURES

Frictional properties: smooth shift performance
Anti-wear protection: extended transmission life

PERFORMANCE

| | | | |
|----------------------|---------------|-------------|--------------|
| ALLISON | C4 | FORD | ESP-M2C166-H |
| CATERPILLAR | TO-2 | FORD | MERCON |
| DAIMLER TRUCK | DTFR 13C120 | GM | DEXRON III-H |
| FORD | ESP-M2C138-CJ | MB | 236.2 |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|-------------------------------|------------|-------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.849 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 32.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 6.82 |
| Viscosity index | ASTM D2270 | | 181 |
| Pour point | ASTM D6892 | °C | -51 |
| Brookfield viscosity at -40°C | ASTM D2983 | mPa.s | 14140 |
| Flash Point COC | ASTM D92 | °C | 198 |
| Colour | VISUAL | | RED |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

