

IN-OUTBOARD 4T 25W40

12/08/2023
1956

This is a semi-synthetic 4-stroke motor oil, specifically designed to meet the requirements of the NMMA FC-W specification. This oil procures an increased protection against corrosion, even in a salt water environment. It also contains a unique anti-wear package based on molybdenum/zinc technology.

APPLICATIONS

This oil is specifically destined for the lubrication of modern 4-stroke outboard and inboard engines (e.g. Mercury Marine, Yamaha). These applications are usually described as "sterndrive & inboard". It can also be used in older 4-stroke outboard engines.

FEATURES

Total engine protection: Outstanding engine cleanliness and durability

PERFORMANCE

API	SJ	NMMA	FC-W
API	SL		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	91.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.8
Viscosity index	ASTM D2270		155
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.4
Pour point	ASTM D6892	°C	-39
CCS viscosity at -10°C	ASTM D5293	mPa.s	6100
Flash Point COC	ASTM D92	°C	222

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION