

WOLF OFFICIALTECH OW20 C6 F

11/08/2023
65645

This is a full synthetic lubricant mandatory for the newest engines requiring ACEA C6. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest C6 standard (can be used where ACEA C5 is recommended). A standard where protection against LSPI, offering fuel economy and CO2 reduction are important. Its also designed to meet the newest FORD WWS-M2C952-A1 specification which is needed for the recent FORD Ecoblue engines (diesel).

FEATURES

Fuel economy: superior fuel economy and CO2 reduction.

Cold start: excellent fluidity at low temperature.

Aftertreatment protection: full aftertreatment device protection

PERFORMANCE

ACEA	C5	JAGUAR-LAND ROVER	approval STJLR.03.5006
ACEA	C6	JEEP	.
API	SN Plus	KIA	.
API	SP	LEXUS	.
ILSAC	GF-6 A	LINCOLN	.
ACURA	.	MAZDA	.
ASTON MARTIN	.	MB	approval 229.71
BUICK	.	MG	.
CADILLAC	.	MITSUBISHI	.
CHEVROLET	.	NISSAN	.
CHRYSLER	.	OPEL	OV 040 1547 - A20
DODGE	.	PERODUA	.
Fiat	.	ROEWE	.
FORD	WSS-M2C952-A1	SCION	.
GM	DexosD™	SUBARU	.
GMC	.	SUZUKI	.
HONDA	.	TATA	.
HYUNDAI	.	TIANJIN	.
INFINITI	.	TOYOTA	.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	39.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		191
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Density at 15°C	ASTM D4052	g/ml	0.843
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

