

WOLF OFFICIALTECH OW20 C6 F

05/03/2025
65645

This is a full synthetic lubricant mandatory for the newest engines requiring ACEA C6. It is developed to prolong the life and maintain the efficiency of emission systems. It is also designed to provide outstanding engine cleanliness, wear protection and strong durability to keep your engine running like new.

APPLICATIONS

This product has been specifically developed to meet the challenging requirements of the latest C6 standard (can be used where ACEA C5 is recommended). A standard where protection against LSPI, offering fuel economy and CO2 reduction are important. Its also designed to meet the newest FORD WWS-M2C952-A1 specification which is needed for the recent FORD Ecoblue engines (diesel).

FEATURES

Fuel economy: superior fuel economy and CO2 reduction.
Cold start: excellent fluidity at low temperature.
Aftertreatment protection: full aftertreatment device protection

SPECIFICATIONS

ACEA	C5	PERODUA	SFU
ACEA	C6	ROEWE	SFU
API	SN Plus	SCION	SFU
API	SP	SUZUKI	SFU
ILSAC	GF-6 A	TATA	SFU
ACURA	SFU	TIANJIN	SFU
ASTON MARTIN	SFU	TOYOTA	SFU
BUICK	SFU		
CADILLAC	SFU		
CHEVROLET	SFU		
CHRYSLER	SFU		
DODGE	SFU		
FIAT	SFU		
FORD	WSS-M2C952-A1		
GM	DexosD™		
GMC	SFU		
HONDA	SFU		
INFINITI	SFU		
JAGUAR-LAND ROVER	approval STJLR.03.5006		
KIA	SFU		
LEXUS	SFU		
LINCOLN	SFU		
MAZDA	SFU		
MB	approval 229.71		
MG	SFU		
MITSUBISHI	SFU		
OPEL	OV 040 1547 - A20		

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com



TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.843
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	39.8
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.3
Viscosity index	ASTM D2270		191
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	9.4
Pour point	ASTM D6892	°C	-45
Flash Point COC	ASTM D92	°C	234

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

