

# WOLF GUARDTECH 15W50 SL/CF

05/03/2025  
14138

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This oil distinguishes itself by a higher temperature performance and resistance against ageing. Its adapted composition ensures optimal cleanliness of the engine in all conditions. The oil protects the catalyst and ensures optimal engine protection.

## APPLICATIONS

This oil was specially developed for the lubrication of all 4-stroke gasoline or diesel, supercharged (turbo) or naturally aspirated and fulfills the latest norms of the manufacturers.

## FEATURES

Total engine protection: good engine protection and cleanliness

## SPECIFICATIONS

ACEA	A3/B3-10	API	SL/CF
ACEA	A3/B4-08	MB	229.1

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.880
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	134
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	18.0
Viscosity index	ASTM D2270		150
B.N. (HCL04 method)	ASTM D2896	mg KOH/g	8.3
Pour point	ASTM D6892	°C	-39
CCS viscosity at -20°C	ASTM D5293	mPa.s	6600
Sulfated Ash	ASTM D874	Mass %	1.03
Flash Point COC	ASTM D92	°C	225

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

