

# CHAMPION PNEUMA ISO 32

*This oil is destined for the lubrication of pneumatic tools. It contains additives to enhance adhesion, anti-rust activity and an emulsifier to absorb moisture that can be present in the oil. Furthermore, it contains anti-wear and extreme-pressure additives.*

## APPLICATIONS

*This lubricant can be used in tools driven by compressed air, like for instance drilling equipment. This ISO 32 grade can be used in high-speed tools.*

## FEATURES

*Extreme pressure properties: good EP properties*

*Anti-foam properties: adequate anti-foam performance*

## PERFORMANCE

**DIN** 51502 D **ISO** 6743-11 CLASS LP

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	33.1
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	5.82
Viscosity index	ASTM D2270		119
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	208

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

