CHAMPION OEM SPECIFIC 5W30 C3 RN

This synthetic engine oil formulation guarantees a cleaner and better performing engine without lowering the oil drain interval. The broad applicability of this lubricant enables you to offer perfect maintenance to different vehicles of several major brands.

APPLICATIONS

This engine oil can be used in systems with or without exhaust gas aftertreatment where C3 engine oils are required. Furthermore, this engine oil has the official Renault RN 17 approval. This means also that you can use this lubricant where RN0700 & RN0710 were previously required, enabling you to service several Dacia and Renault models with this engine oil.

FEATURES

Broad coverage: reduced lubricant costs.

Significant friction reduction: improved fuel efficiency and lowered emissions.

Excellent engine cleanliness: outstanding engine protection during the entire oil drain interval.

SPECIFICATIONS

ACEA C3 RENAULT RN17

MB approval 226.52

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|----------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.849 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 60.3 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 11.8 |
| Viscosity index | ASTM D2270 | | 197 |
| B.N. (HCLO4 method) | ASTM D2896 | mg KOH/g | 8.0 |
| Pour point | ASTM D6892 | °C | -39 |
| Sulfated Ash | ASTM D874 | Mass % | 0.78 |
| Flash Point COC | ASTM D92 | °C | 226 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

