

# WOLF AROW

## HV ISO 15

14/04/2025  
4403

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation, and quick air release.

### APPLICATIONS

This oil is suitable for hydraulic systems, functioning at variable temperatures and high pressures. It can also be used in gear boxes, which require an oil with a high viscosity index and assuring mechanical and chemical stability. Applicable for regulation systems and hydraulic steering.

### FEATURES

Anti-wear and oxidation stability: superior protection  
Anti-foam properties: excellent anti-foam properties  
Temperature stability: superior viscosity stability

### SPECIFICATIONS

AFNOR	NF E 48-603 HV	ISO	6743-4, HV
AFNOR	NF E 48-690	DENISON	HF-2
AFNOR	NF E 48-691	EATON VICKERS	I-286-S
DIN	51524 Part 3	EATON VICKERS	M-2950-S
ISO	11158, HV		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.841
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	15.8
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	4.1
Viscosity index	ASTM D2270		172
A.N. (Colorimetric)	ASTM D974	mg KOH/g	0.28
Pour point	ASTM D6892	°C	-39
Flash Point COC	ASTM D92	°C	162

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

