

# WOLF MULTIPURPOSE GREASE 3

25/09/2026  
9103

This is a lubricating grease for general applications, where no specific requirements are made. This grease has a good oxidation stability, so that it can ensure long-lasting lubrication. It is water-resistant and has good temperature characteristics. Therefore it can be used at high temperatures and it stays pumpable at low temperatures making it suitable for bearing lubrication.

## APPLICATIONS

This grease can be used in both industrial and automotive applications. It is suitable for a wide range of plain and rolling bearings. Temperature range: -30°C to +120°C, Max. +130°C

## FEATURES

Stability: good mechanical stability  
Corrosion protection: good corrosion protection  
Water resistance: suitable also in wet environment

## SPECIFICATIONS

|     |        |     |          |
|-----|--------|-----|----------|
| DIN | 51502  | ISO | 6743     |
| DIN | K3K-30 | ISO | L-XCCFA3 |

## TYPICAL CHARACTERISTICS

| Test                            | Method                    | Unit   | Average results |
|---------------------------------|---------------------------|--------|-----------------|
| Texture                         | Visual                    |        | Smooth          |
| Colour                          | VISUAL                    |        | Light Brown     |
| NLGI Classification             | ASTM D217                 |        | 3               |
| Worked Penetration (60 strokes) | ISO 2137                  | 0.1 mm | 235             |
| Dropping point                  | ISO 2176/IP 396           | °C     | 190             |
| Four Ball Weld Load             | ASTM D2596/<br>DIN51350:4 | N      | 2000            |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.