

CHAMPION PRORACING GP 2T ESTER +

This full synthetic engine oil suits the needs of the most demanding two-stroke motorcycles. Its Ester+ Adaptive Shield Technology surpasses the limits of conventional ester full synthetic products. This innovative formulation offers outstanding lubricating properties, including reduced wear, which directly improve component protection and reduce engine friction.

APPLICATIONS

This motorcycle engine oil exceeds the standards of API TC, TC+, ISO L-EGB and JASO FB; extending its applicability to a wide range of 2-stroke off-road motorcycles and sport bikes. It is used for mixed lubrication and is not suitable for separate lubrication.

FEATURES

Champion Ester+ Adaptive Shield Technology: outstanding engine performance.

PERFORMANCE

API	TC	ISO	L-EGB
API	TC+	JASO	FB

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.911
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	111
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	15.1
Viscosity index	ASTM D2270		142
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	2.9
Flash Point COC	ASTM D92	°C	240
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

