

# WOLF S.T.O.U. 10W40

11/08/2023  
1426

This is a semi synthetic lubricant based on carefully selected highly refined base oils for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

## APPLICATIONS

These oil is recommended for the lubrication of charged and uncharged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment.

## FEATURES

Anti-wear and oxidation stability: proven protection of critical parts  
Cold start: excellent fluidity at low temperature

## PERFORMANCE

|         |                              |    |           |
|---------|------------------------------|----|-----------|
| ACEA    | E3                           | MF | M 1135    |
| API     | CG-4                         | MF | M 1139    |
| API     | GL-4                         | MF | M 1143    |
| API     | GL-5 (Low speed/high torque) | MF | M 1144    |
| API     | SF/CE                        | NH | NH 024C   |
| DIN     | 51524 T3 HVLPD               | NH | NH 410B   |
| ALLISON | C4 (Agriculture applic.)     | NH | NH 420A   |
| CASE    | MAT 3525                     | ZF | TE-ML 03A |
| CASE    | MAT 3526                     | ZF | TE-ML 05K |
| FORD    | ESN-M2C134 C/D               | ZF | TE-ML 06A |
| FORD    | ESN-M2C159 B/C               | ZF | TE-ML 06B |
| FORD    | FNH 82009203                 | ZF | TE-ML 06C |
| JD      | J20C                         | ZF | TE-ML 07B |
| JD      | J27                          | ZF | TE-ML 07D |
| MF      | approval M 1145              |    |           |

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)



## TYPICAL CHARACTERISTICS

| Test                         | Method     | Unit  | Average results |
|------------------------------|------------|-------|-----------------|
| Density at 15°C              | ASTM D4052 | g/ml  | 0.868           |
| Kinematic viscosity at 40°C  | ASTM D445  | mm²/s | 88.2            |
| Kinematic viscosity at 100°C | ASTM D445  | mm²/s | 13.8            |
| Viscosity index              | ASTM D2270 |       | 160             |
| Pour point                   | ASTM D6892 | °C    | -36             |
| CCS viscosity at -25°C       | ASTM D5293 | mPa.s | 6700            |
| Flash Point COC              | ASTM D92   | °C    | 220             |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolflubes.com](http://www.wolflubes.com)

