

# CHAMPION PRORACING GP FORK OIL 10W

This 10W synthetic blend fork oil has an extremely high viscosity index, offering optimal dampening control over a wide range of temperatures. Furthermore, this lubricant extends the service life of your motorcycle by combining quick air release and elastomer compatibility with anti-corrosion and anti-wear properties.

## APPLICATIONS

This fork oil is specifically developed for universal usage in forks and dampers of bikes and mopeds. It is suitable for on- and off-road conditions. The choice between the different fork oil grades is to be made according to ambient temperatures, riding patterns and dampening effect. Please follow the manufacturer's instructions.

## FEATURES

*Dampening control: smoother ride*

*Balanced protective properties: extended lifespan*

*Broad material compatibility: fewer fluids required to maintain several motorcycles*

## SPECIFICATIONS

DIN 51524 Part 3

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.848
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	35.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	7.4
Viscosity index	ASTM D2270		185
Pour point	ASTM D6892	°C	-51
Colour	VISUAL		BLUE

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

