

ANTI-FREEZE

11/08/2023
5020

An undiluted on mono-ethyleneglycol based fluid with anti-corrosion inhibitors. It offers total and permanent protection of the cooling system. It contains no nitrates, phosphates, or amines.

APPLICATIONS

Cooling circuits of the open or closed type (vehicles and heating). Dilute with demineralised water. Protection temperature: -20 °C needs 27% AF // -24 °C needs 40% AF // -38 °C needs 50% AF.

FEATURES

Anti-corrosion properties: complete system protection

PERFORMANCE

| | | | |
|-------|-------------|-----|-----------|
| AFNOR | 15-601/1991 | BS | 6580-1992 |
| ASTM | D3306 | SAE | J1034 |
| ASTM | D4985 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|----------------------------|------------|-------------|-----------------|
| Freezing point 50% vol. AF | ASTM D1177 | °C | -37 |
| Reserve alkalinity | ASTM D1121 | ml 0.1M HCl | 21.1 |
| Density at 20°C | ASTM D4052 | g/ml | 1.128 |
| Colour | VISUAL | | Blue |
| Water content | ASTM D1123 | % wt/wt | 3.5 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION