11/08/2023 70312

# WOLF DIESEL PARTICULATE

This product is an organo-metallic diesel fuel additive to be used as a catalyst for the regeneration of diesel particulate filters. It lowers the ignition temperature of soot collected in the diesel particulate filter and optimizes periodic combustion of accumulated soot, a process known as filter regeneration. Prevents performance loss caused by clogged diesel particulate filters and incomplete combustion of soot. Extends lifetime of the expensive diesel particulate filter.

### **APPLICATIONS**

For all diesel engines (including common rail and turbo charged engines) with standard or retrofitted diesel particulate filter. Pour the content of one bottle in the fuel tank before filling it with fuel. One bottle (325ml) treats 40-60 liters of diesel fuel.

### **FEATURES**

Cleaning action: regenerates the DPF and extends its life

#### PERFORMANCE

/

## **TYPICAL CHARACTERISTICS**

/

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.825
Kinematic viscosity at 40°C	ASTM D445	mm²/s	2.21
A.N. (Colorimetric)	ASTM D974	mg KOH/g	1.8
Flashpoint PMCC	ASTM D93	°C	70

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

