

CHAMPION ACTIVE DEFENCE ATF D

This is an oil, with a high viscosity index, especially designed to satisfy the requirements of General Motors for the use in the first generation of automatic transmissions. Very good anti-wear and detergent qualities, anti-foam and anti-corrosion.

APPLICATIONS

This oil is used in automatic transmissions, power steering, torque convertors and hydraulic systems.

FEATURES

Anti-wear protection: long transmission life
Extended oil life: optimized thermal and oxidation stability

SPECIFICATIONS

DIN	HLP-D	DTR	13C120
ALLISON	C2/C3	GM	6032-M DEXRON
ATF	TYPE A SUFFIX A	MB	236.2

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Color	ASTM D1500		red
Density at 15°C	ASTM D4052	g/ml	0.858
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	37.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	7.6
Viscosity index	ASTM D2270		179
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	2.1
Pour point	ASTM D6892	°C	-45
Brookfield viscosity at -40°C	ASTM D2983	mPa.s	50.000

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium
Tel. +32 3 870 00 00
www.championlubes.com

