

PNEUMA ISO 32

This oil is destined for the lubrication of pneumatic tools. It contains additives to enhance adhesion, anti-rust activity and an emulsifier to absorb moisture that can be present in the oil. Furthermore, it contains anti-wear and extreme-pressure additives.

APPLICATIONS

This lubricant can be used in tools driven by compressed air, like for instance drilling equipment. This ISO 32 grade can be used in high-speed tools.

FEATURES

Extreme pressure properties : good EP properties.

Anti-foam properties : adequate anti-foam performance.

SPECIFICATION LEVEL

DIN 51502 D **ISO** 6743-11 CLASS LP

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.876
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	33.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	5.82
Viscosity index	ASTM D2270		119
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	208

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION®