

CHAMPION OIL LEAK STOP

This product prevents and stops oil leakage through the seals. It makes seals swell back to their original size and regain pliability. It improves the viscosity of the motor oil and optimizes engine performance by enhancing motor compression.

APPLICATIONS

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters. Add the contents of one bottle to the warm oil. Make sure not to exceed the maximum oil level in the engine. One bottle (325ml) treats a crankcase of 3-6 liters.

FEATURES

Reduction of oil leakage: restores sealing and prevents leakage

PERFORMANCE

/ /

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.896
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	79.1
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	10.5

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

