

# CHAMPION COMPETE

## ISO 46

A mineral oil specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

### APPLICATIONS

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

### FEATURES

Anti-wear and oxidation stability: superior protection.

Anti-foam properties: excellent anti-foam properties.

Temperature stability: adequate viscosity stability.

### PERFORMANCE

<b>DIN</b>	51524 Part 2	<b>ISO</b>	6743-4, HM
<b>ISO</b>	11158, HM		

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.875
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	46.0
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	6.85
Viscosity index	ASTM D2270		105
Pour point	ASTM D6892	°C	-30
Flash Point COC	ASTM D92	°C	216

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

