

HYDRAULIC XHV 28 ARCTIC

12/08/2023
24500

Thanks to its stable mineral and synthetic base oils and the advanced additive package, this four-stroke motorcycle engine oil guarantees a smooth and stable ride. The balanced formula is developed to exactly suit the needs of motorcycle enthusiasts looking for optimal riding comfort.

APPLICATIONS

This lubricant is developed for the engines, transmissions and wet clutches of four-stroke motorcycles. It is perfectly balanced to meet the requirements of several manufacturers.

FEATURES

Extended motorcycle lifespan thanks to the oil's protective properties.: superior protection

Protects the original riding comfort.: excellent anti-foam properties

Simpler fluid management thanks to the oil's broad applicability.: extreme viscosity stability

PERFORMANCE

AFNOR	NF E 48-603 HV	ISO	6743-4, HV
AFNOR	NF E 48-690	DENISON	HF-2
AFNOR	NF E 48-691	EATON VICKERS	I-286-S
DIN	51524 T3 HVLP	EATON VICKERS	M-2950-S
ISO	11158, HV		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.847
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	29.5
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	8.87
Viscosity index	ASTM D2270		306
Pour point	ASTM D6892	°C	-51
Flash Point COC	ASTM D92	°C	152

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfoil.com

WOLFOIL
CORPORATION