

CHAMPION HYDRO HV ISO 32

A high viscosity index paraffinic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. Superior performance in keeping the system clean by reducing the formation of deposits. It also demonstrates good filterability, water separation, and quick air release.

APPLICATIONS

This oil is suitable for hydraulic systems, functioning at variable temperatures and high pressures. It can also be used in gear boxes, which require an oil with a high viscosity index and assuring mechanical and chemical stability. Applicable for regulation systems and hydraulic steering.

FEATURES

Anti-wear and oxidation stability: superior protection

Anti-foam properties: excellent anti-foam properties

Temperature stability: superior viscosity stability

PERFORMANCE

| | | | |
|--------------|----------------|----------------------|-----------------------|
| AFNOR | NF E 48-603 HV | ISO | 6743-4, HV |
| AFNOR | NF E 48-690 | CINCINNATI | MACHINE P-68 [ISO 32] |
| AFNOR | NF E 48-691 | DENISON | HF-0, HF-1, HF-2 |
| DIN | 51524 Part 3 | EATON VICKERS | I-286-S |
| ISO | 11158, HV | EATON VICKERS | M-2950-S |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|-------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.869 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 32.7 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 6.3 |
| Viscosity index | ASTM D2270 | | 147 |
| Pour point | ASTM D6892 | °C | -39 |
| Flash Point COC | ASTM D92 | °C | 204 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

www.championlubes.com

