

# WOLF OFFICIALTECH OW30 MS-BFE

14/04/2025  
65619

This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is specifically formulated to meet the BMW Longlife-12 FE specification. It is adapted to meet the requirements of the latest technology, highly engineered turbo engines requiring high performance and lower viscosity oils.

## APPLICATIONS

This product is mandatory in the newest BMW gasoline and diesel engines. It provides a multi vehicle application through the ACEA C2 specification. Optimum formulation for today's cars with exceptional film strength preventing oil film breakdown and reducing friction providing fuel economy and reliability.

## FEATURES

Total engine protection: performance in keeping the engine clean  
Fuel economy: superior fuel economy and CO2 reduction  
Cold start: excellent fluidity at low temperature

## SPECIFICATIONS

ACEA	C2	ILSAC	GF-5
API	SN	BMW	LONGLIFE-12FE

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.841
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	53.7
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.1
Viscosity index	ASTM D2270		178
Pour point	ASTM D6892	°C	-57
Sulfated Ash	ASTM D874	Mass %	0.80
Flash Point COC	ASTM D92	°C	225
CCS viscosity at -35°C	ASTM D5293	mPa.s	5400
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	8.3

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.