

AROW ISO 22

13/01/2017
4004

A mineral oil, specifically designed to meet the requirements of most important manufacturers of hydraulic equipment. It contains anti-wear, anti-oxidant, anti-corrosion and anti-foam additives.

KÄYTTÖKOHTEET

This oil is specifically designed to satisfy the requirements of the manufacturers of hydraulic systems where the highest demands are made concerning high pressure, temperatures or speeds. It is recommended for the hydraulic systems of the following types : Vickers, Gerotor, Gresen, HPM, Denison, Cessna, Hydreco and Worthington. It is also suitable for the lubrication of workshop equipment, reducing gears, bearings, compressed air systems and air screw compressors.

OMINAISUUDET

Anti-wear and oxidation stability : superior protection.
Anti-foam properties : excellent anti-foam properties.
Temperature stability : adequate viscosity stability.

MÄÄRITYSTASO

AFNOR	NF E 48-603 HM
AFNOR	NF E 48-690
AFNOR	NF E 48-691
DENISON	HF-2
DIN	51524 Part 2
EATON VICKERS	I-286-S
EATON VICKERS	M-2950-S
ISO	11158, HM
ISO	6743-4, HM

TYYPILLISET OMINAISUUDET

Testi	Menetelmä	Yksikkö	Keskimääräinen tulos
Tiheys lämpötilassa 15 °C	ASTM D4052	g/ml	0.865
Kinemaattinen viskositeetti lämpötilassa 40 °C	ASTM D445	mm²/s	21.3
Kinemaattinen viskositeetti lämpötilassa 100 °C	ASTM D445	mm²/s	4.4
Viskositeetti-indeksi	ASTM D2270		117
Jähmepiste	ASTM D6892	°C	-30
Leimahduspiste (COC)	ASTM D92	°C	195

Pidätämme oikeuden muuttaa tuotteidemme yleisominaisuuksia, jotta asiakkaamme voivat hyödyntää uusimpia teknisiä uudistuksiamme.

WOLF OIL CORPORATION NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00
www.wolflubes.com

THE VITAL LUBRICANT

The WOLF brand and design are registered trademarks of Wolf Oil Corporation NV