11/08/2023 1925

WOLF OUTBOARD 4T 10W30

This is a semi synthetic lubricant based on carefully selected highly refined base oils. This 4-stroke motor oil is specifically designed to meet the requirements of the NMMA FC-W specification. This oil procures an increased protection against corrosion, even in a salt water environment. It also contains a unique anti-wear package based on molybdenum/zinc technology.

APPLICATIONS

This oil is specifically destined for the lubrication of modern 4-stroke outboard engines (e.g. Mercury Marine, Yamaha). It can also be used in older 4-stroke outboard engines.

FEATURES

Total engine protection: outstanding engine cleanliness and durability

PERFORMANCE

API	SJ	NMMA	approval FC-W
API	SL		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.855
Kinematic viscosity at 40°C	ASTM D445	mm²/s	74.0
Kinematic viscosity at 100°C	ASTM D445	mm²/s	12.0
Viscosity index	ASTM D2270		159
B.N. (HCLO4 method)	ASTM D2896	mg KOH/g	7.4
CCS viscosity at -25°C	ASTM D5293	mPa.s	4010
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

