

WOLF ELECTRUM BRAKE FLUID

11/08/2023
65360

This low viscosity brake fluid is especially recommended for use in hydraulic brake and clutch systems of vehicles fitted with ESP (Electronic Stability Program) and ABS (Anti-lock Braking System) with a high boiling point and outstanding performance at very low temperatures.

APPLICATIONS

Its high wet boiling point (172°C) is superior to conventional fluids DOT 3 and DOT 4 and therefore enables longer product lifetime. The viscosity at - 40 °C of this exceptional brake fluid is lower than conventional brake fluids allowing an easier fluid circulation in micro-valves of anti-locking systems for better response of ESP, ABS and ASR systems in electric, hybrid and other vehicles.

FEATURES

Boiling point: very high boiling point, safe braking.

Anti-corrosion properties: complete brake system protection.

PERFORMANCE

FMVSS	116 DOT 4	SAE	J 1703
FMVSS	116 DOT3	SAE	J 1704
ISO	4925 Class 3,4&6		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Appearance	Visual		C&B
Water content	DIN 51777 T1	ppm	< 2000
pH	ASTM D1287		8.53
Wet Equilibrium Reflux Boiling Point (WERBP)	ASTM D1120	°C	172

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolflubes.com

