

WOLF GUARDTECH 15W40 SF/CD

11/08/2023
1336

Multigrade engine oil for the lubrication of gasoline and diesel engines of passenger cars with natural aspiration or turbocharging. This oil is characterized by a combination of good detergent and dispersion properties, together with a low ash content.

APPLICATIONS

This oil is suitable for the lubrication of gasoline and diesel engines, with or without turbo from 1980 to 1989.

FEATURES

Total engine protection: engine protection and cleanliness

PERFORMANCE

API	SF/CD	MB	226.1
MIL	L-46152 B		

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.864
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	105
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	14.0
Viscosity index	ASTM D2270		135
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	5.9
Pour point	ASTM D6892	°C	-36
CCS viscosity at -20°C	ASTM D5293	mPa.s	6340
Flash Point COC	ASTM D92	°C	218

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolfubes.com

