

# GUARDTECH

## SAE 30 CF-4/SG

07/08/2019  
21203

Universal mineral oil of high quality, suitable for diesel engines (supercharged or naturally aspirated) and gasoline engines operating in cold climatic conditions.

### APPLICATIONS

This oil is particularly recommended for fixed diesel engines, material for public works and mixed fleets of trucks and cars.

### FEATURES

Total engine protection : performance in keeping the engine clean.

### SPECIFICATION LEVEL

ACEA	E2/E1	MIL	MIL-L-2104 E
ALLISON	C4	MIL	MIL-L-46152 E
API	CF-4/SG	MTU	Oil Category 1
CATERPILLAR	TO-2	ZF	TE-ML 03A
MAN	270	ZF	TE-ML 04A
MB	227.0	ZF	TE-ML 04B
MB	228.0	ZF	TE-ML 07D

### TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.890
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	103
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	11.8
Viscosity index	ASTM D2270		103
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	7.0
Pour point	ASTM D6892	°C	-42
Sulfated Ash	ASTM D874	Mass %	0.88
Flash Point COC	ASTM D92	°C	235

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

#### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolf lubes.com](http://www.wolf lubes.com)

