11/08/2023 3012

WOLF OFFICIALTECH ATF LIFE PROTECT 6

This is a full synthetic lubricant based on carefully selected very high quality base oils that has been specifically developed for ZF 6-speed automatic transmissions. Its particular formulation ensures a trouble-free operation and smooth gear shifting.

APPLICATIONS

Mainly intended for the ZF-6 speed automatic transmissions, as fitted in BMW, Jaguar and Land Rover, it is also suitable for other OEMs, who recommend this type of fluid (e.g. Audi Quattro).

FEATURES

Anti-wear protection: significantly extended transmission life Frictional properties: very smooth gear shifting, no vibration Extended oil life: excellent thermal and oxidation stability

PERFORMANCE

| AML | 4G4319A509/AA/S | HYUNDAI | 040000C90SG |
|---------|-----------------|------------|-------------|
| BENTLEY | PY112995PA | JAGUAR | Fluid 8432 |
| BMW | 83 22 2 305 396 | LAND ROVER | TYK500050 |
| BMW | 83220142516 | MASERATI | 231603 |
| BMW | ATF 2 | VW | G 055 005 |
| BMW | M-1375.4 | ZF | TE-ML 11 |

TYPICAL CHARACTERISTICS

| Method | Unit | Average results |
|------------|--|---|
| ASTM D4052 | g/ml | 0.850 |
| ASTM D445 | mm²/s | 31.0 |
| ASTM D445 | mm²/s | 6.17 |
| ASTM D2270 | | 152 |
| ASTM D6892 | °C | -48 |
| ASTM D2983 | mPa.s | <=20000 |
| ASTM D92 | °C | 202 |
| VISUAL | | AMBER |
| | ASTM D4052 ASTM D445 ASTM D445 ASTM D2270 ASTM D6892 ASTM D2983 ASTM D92 | ASTM D4052 g/ml ASTM D445 mm²/s ASTM D445 mm²/s ASTM D2270 ASTM D6892 °C ASTM D2983 mPa.s ASTM D92 °C |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

