ACTIVE DEFENCE SAE 40

This is a straight mineral oil, made of highly refined base oils.

ZASTOSOWANIA

Non-detergent engine oil, also for not heavily loaded gearboxes. Lubrication by hand (oilcan). Lubrication of air compressors with low discharge temperatures or when an oil of DIN-VC-class is required.

CECHY

Total engine protection: engine protection and cleanliness.

SPECYFIKACJA

API SA

TYPOWE CECHY

Test	Metoda	Jednostka	Średni wynik
Gęstość w temp. 15°C	ASTM D4052	g/ml	0.891
Lepkość kinematyczna przy temp. 40°C	ASTM D445	mm²/s	140
Lepkość kinematyczna w temp. 100°C	ASTM D445	mm²/s	13.7
Indeks lepkości	ASTM D2270		93
Temperatura krzepnięcia	ASTM D6892	°C	-12
Tempera zapłonu metodą Clevelanda	ASTM D92	°C	260

Zastrzegamy sobie prawo do modyfikowania ogólnych charakterystyk naszych produktów, aby umożliwić naszym klientom czerpanie maksymalnych korzyści z najnowszych odkryć techniki.

CHAMPION CHEMICALS NV
G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 3 870 00 00
www.championlubes.com

The CHAMPION brand and design are registered trademarks of Champion Chemicals NV - Made in Belgium