

PROPULSE TT 2TESTER

This ester-based synthetic blend motorcycle oil has been developed especially for two-stroke motorcycles. Its groundbreaking additive technology increases both engine performance and protects all lubricated parts completely. This powerful formulation covers a large part of the two-stroke motorcycle market thanks to its high-end properties.

APPLICATIONS

This motorcycle engine oil exceeds the standards of API TC, ISO L-EGD and JASO FC/FD; extending its applicability to a wide range of 2-stroke off- and on-road motorcycles.

FEATURES

Improved engine performance.

Recommended product for touring & daily riding.

Easier fluid management thanks to the oil's broad applicability.

SPECIFICATION LEVEL

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	79.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		135
B.N. (HClO ₄ method)	ASTM D2896	mg KOH/g	1.1
Flash Point COC	ASTM D92	°C	88
Colour	VISUAL		RED

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

CHAMPION[®]