

CHAMPION PNEUMA ISO 22

This oil is used for the lubrication of pneumatic tools. It contains additives to improve adhesion and anti-rust, and an emulsifier to absorb moisture. It also contains anti-wear and extreme-pressure additives.

APPLICATIONS

This lubricant is used in tools driven by compressed air, like for instance drilling equipment. This ISO 22 grade is especially suited for very low ambient temperatures.

FEATURES

Extreme pressure properties: good EP properties

Anti-foam: adequate anti-foam performance

PERFORMANCE

DIN 51502 D **ISO** 6743-11 CLASS LP

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.862
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	22.0
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	4.65
Viscosity index	ASTM D2270		131
Pour point	ASTM D6892	°C	-33
Flash Point COC	ASTM D92	°C	200

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

