

# CHAMPION COMPETE SL/CF 10W40 B4

This engine oil meets the core requirements of ACEA and API for passenger cars. It offers excellent engine cleanliness and complete protection to all engine components.

## APPLICATIONS

Suitable for gasoline and diesel engines with standard aspiration and superchargers. Particularly recommended for direct injection diesel engines, including common rail direct fuel injection systems.

## FEATURES

Performance in keeping the engine clean.: Performance in keeping the engine clean.

## PERFORMANCE

<b>ACEA</b>	A3/B3-16	<b>MB</b>	229.1
<b>ACEA</b>	A3/B4	<b>VW</b>	501 01
<b>API</b>	SL/CF	<b>VW</b>	505 00

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.865
Kinematic viscosity at 40°C	ASTM D445	mm²/s	90.1
Kinematic viscosity at 100°C	ASTM D445	mm²/s	13.8
Viscosity index	ASTM D2270		155
B.N. [HCL04 method]	ASTM D2896	mg KOH/g	10.1
Pour point	ASTM D6892	°C	-33
Evaporation loss [Noack]	CEC L-040-93[B]	% M/M	10.0

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

