

WOLF OFFICIALTECH OW30 LL III FE

29/04/2024
65620

This is a full synthetic lubricant based on carefully selected very high quality base oils. It is specifically formulated to meet the most demanding VW specifications available today - VW 504.00 and 507.00 - as well as the Long Life III requirements of the VAG Group. It is a Mid SAPS oil which meets Euro 4, 5 and 6 norms and provides protection to the Diesel Particulate Filter. This viscosity grade provides a proven fuel economy over a 5W30 grade.

APPLICATIONS

Backwards compatible: 504.00 and 507.00 supersedes all previous VW specifications (502.00, 503.00, 503.01, 505.00, 506.00 and 506.01). All vehicles in the VAG Group (Volkswagen, Audi, Seat, Skoda) with extended oil drain intervals (30.000 km or 2 years) from 2007 onwards. Note: For V10 TDI and 5-cylinder 2.5 TDI engines, prior to 2007, where the 506.01 specification has to be used, this oil is not recommended. The first generation engines with pump injector units should use the 505.01 specification.

FEATURES

Aftertreatment protection: Full aftertreatment system protection.
Total engine protection: Outstanding engine cleanliness and durability.
Fuel economy: Lower fuel consumption and CO2 emissions.

SPECIFICATIONS

| | | | |
|------|----------------------|---------|------------------------|
| ACEA | C2 | MB | 229.31 |
| ACEA | C3 | MB | approval 229.51 |
| BMW | approval LONGLIFE-04 | PORSCHE | approval C30 |
| FIAT | 9.55535-DS1 | VW | approval 504 00/507 00 |
| FIAT | 9.55535-GS1 | VW | TL 525 45 |
| FIAT | 9.55535-S3 | | |

TYPICAL CHARACTERISTICS

| Test | Method | Unit | Average results |
|------------------------------|------------|----------|-----------------|
| Density at 15°C | ASTM D4052 | g/ml | 0.842 |
| Kinematic viscosity at 40°C | ASTM D445 | mm²/s | 59.0 |
| Kinematic viscosity at 100°C | ASTM D445 | mm²/s | 11.7 |
| Viscosity index | ASTM D2270 | | 197 |
| B.N. (HClO4 method) | ASTM D2896 | mg KOH/g | 8.3 |
| Pour point | ASTM D6892 | °C | -48 |
| Colour | VISUAL | | Brown |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium
Tel. +32 (0)3 870 00 00

www.wolf lubes.com

