

# MULTIGRADE MS-FE SAE 5W20

28/03/2024  
65612

*This is a full synthetic lubricant based on carefully selected very high quality base oils. This oil is extremely fuel-efficient and meets the requirements of the new Ford EcoBoost petrol engines. It ensures a reduction of fuel consumption on partial and full load operation as well as reduction of exhaust emission. It has excellent cold starting behavior giving a very good operating reliability.*

## APPLICATIONS

Meets the requirements of the Ford WSS-M2C948-B specification and is mandatory for Ford EcoBoost 1.0 3-cylinder engines and is required for further EcoBoost petrol engines. This oil can also be used where the vehicle manufacturer specifies a motor oil ACEA A1/B1 or API SN.

## FEATURES

Total engine protection: performance in keeping the engine clean

Fuel economy: superior fuel economy and CO2 reduction

Cold start: excellent fluidity at low temperature

## SPECIFICATIONS

ACEA	A1/B1-12	FORD	WSS-M2C925-A
ACEA	C5	FORD	WSS-M2C925-B
API	SN/RC	FORD	WSS-M2C948-A
ILSAC	GF-5	FORD	WSS-M2C948-B
CHRYSLER	MS 6395	JAGUAR-LAND ROVER	STJLR.03.5004

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.851
Kinematic viscosity at 40°C	ASTM D445	mm²/s	42.3
Kinematic viscosity at 100°C	ASTM D445	mm²/s	7.9
Viscosity index	ASTM D2270		162
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	7.6
Pour point	ASTM D6892	°C	-39
CCS viscosity at -30°C	ASTM D5293	mPa.s	5500
Sulfated Ash	ASTM D874	Mass %	0.8
Flash Point COC	ASTM D92	°C	220

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### WOLF OIL CORPORATION NV

G. Gilliotstraat 52 – 2620 Hemiksem – Belgium  
Tel. +32 (0)3 870 00 00

[www.wolfoil.com](http://www.wolfoil.com)

**WOLFOIL**  
CORPORATION