

CHAMPION SYNTH 2T

This is a full synthetic lubricant based on carefully selected very high quality base oils for air cooled 2-stroke gasoline engines. This oil is specifically designed for two-stroke engines of motorcycles with mixed or separate lubrication. It assures a remarkable cleanliness of the engine, and has a high lubricity and a high thermal stability. It substantially avoids the formation of exhaust smoke.

APPLICATIONS

Due to its universal character this lubricant is suitable as well with small displacement engines as with heavy motorcycles. Satisfies the requirements of high specific power engines, such as Kawasaki, Suzuki, Yamaha or Honda.

FEATURES

Engine protection: outstanding engine cleanliness and durability

Corrosion protection: adequate corrosion protection

Smoke suppression: excellent smoke reduction

PERFORMANCE

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.877
Kinematic viscosity at 40°C	ASTM D445	mm ² /s	79.3
Kinematic viscosity at 100°C	ASTM D445	mm ² /s	11.4
Viscosity index	ASTM D2270		135
B.N. [HClO4 method]	ASTM D2896	mg KOH/g	1.1
Pour point	ASTM D6892	°C	-48
Flash Point COC	ASTM D92	°C	88
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

