

# CHAMPION AGRILINE 2T

This is a semi synthetic lubricant based on carefully selected highly refined base oils, which combine a high lubricating power with a minimum of deposits and a very high thermal stability. Prediluted for ease of use. Its special formula reduces the formation of exhaust smoke.

## APPLICATIONS

It can be added by mixing in the gasoline fuel tank, or by separated lubrication. It was specifically developed for the lubrication of 2-stroke engines of gardening material, chain saws and lawn mowers. For the mixing ratio, always follow the manufacturers' recommendations (average: 3%).

## FEATURES

Engine protection: excellent engine performance

Smoke suppression: excellent smoke reduction

Corrosion protection: adequate corrosion protection

## SPECIFICATIONS

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

## TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	73.6
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	10.2
Viscosity index	ASTM D2270		122
B.N. (HClO <sub>4</sub> method)	ASTM D2896	mg KOH/g	1.5
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

### CHAMPION CHEMICALS NV

G. Gilliatstraat 52 - 2620 Hemiksem - Belgium

Tel. +32 3 870 00 00

[www.championlubes.com](http://www.championlubes.com)

