

CHAMPION AGRILINE 2T

This is a semi synthetic lubricant based on carefully selected highly refined base oils, which combine a high lubricating power with a minimum of deposits and a very high thermal stability. Prediluted for ease of use. Its special formula reduces the formation of exhaust smoke.

APPLICATIONS

It can be added by mixing in the gasoline fuel tank, or by separated lubrication. It was specifically developed for the lubrication of 2-stroke engines of gardening material, chain saws and lawn mowers. For the mixing ratio, always follow the manufacturers' recommendations (average: 3%).

FEATURES

Engine protection: excellent engine performance

Smoke suppression: excellent smoke reduction

Corrosion protection: adequate corrosion protection

PERFORMANCE

API	TC	JASO	FC
ISO	L-EGD	JASO	FD

TYPICAL CHARACTERISTICS

Test	Method	Unit	Average results
Density at 15°C	ASTM D4052	g/ml	0.872
Kinematic viscosity at 40°C	ASTM D445	mm²/s	73.6
Kinematic viscosity at 100°C	ASTM D445	mm²/s	10.2
Viscosity index	ASTM D2270		122
B.N. (HClO4 method)	ASTM D2896	mg KOH/g	1.5
Flash Point COC	ASTM D92	°C	106
Colour	VISUAL		BLACKISH GREEN

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

CHAMPION CHEMICALS NV

G. Gilliatstraat 52 – 2620 Hemiksem – Belgium

Tel. +32 3 870 00 00

www.championlubes.com

